

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
14 December 2000 (14.12.2000)

PCT

(10) International Publication Number
WO 00/74776 A1

- (51) International Patent Classification⁷: A61N 1/365 (SE). ANDERSSON, Jonas [SE/SE]; Lidköpingsvägen 30, S-121 39 Johanneshov (SE). LIDMAN, Johan [SE/SE]; Krukmakargatan 63, S-117 41 Stockholm (SE).
- (21) International Application Number: PCT/SE00/01025
- (22) International Filing Date: 22 May 2000 (22.05.2000) (74) Common Representative: ST. JUDE MEDICAL AB; Patent Department, S-175 84 Järfälla (SE).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 9902058-8 3 June 1999 (03.06.1999) SE (81) Designated State (*national*): US.
- (71) Applicant (*for all designated States except US*): ST. JUDE MEDICAL AB [SE/SE]; S-175 84 Järfälla (SE). Published: — *With international search report.*
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): HEDBERG, Sven-Erik [SE/SE]; Odonstigen 5, S-196 32 Kungsängen
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: MEDICAL IMPLANT



(57) Abstract: A medical implant (1) comprising oscillator monitoring means (10) for monitoring the function of an oscillator (2) in the medical implant, and a method of monitoring the function of an oscillator (2) in a medical implant (1). The oscillator (2) produces periodic pulses for use in the operation of the medical implant (1), and the oscillator monitoring means (10) detects a deviation in the function of the oscillator (2) and provides a deviation signal (D) indicating the detection of such a deviation. The medical implant (1) also comprises measuring means (20) for obtaining a physiological parameter emanating from the human body. The measuring means (20) is also provided for generating an electric signal (E) related to a time component of the physiological parameter, and the oscillator monitoring means (10) is connected to the measuring means (20) and uses the electric signal (E) for the deviation detection.

WO 00/74776 A1